

# #1 Network Glaze Clean:

Deglazer & Calcium Deposit Remover SDS Revision Date: 2/17/2015

## 1. Identification Of The Substance / Mixture And Of The Company / Undertaking

### 1.1. Product Identifier

Product Identity **#1 NETWORK GLAZE CLEAN**  
 Deglazer & Calcium Deposit Remover  
 Alternate Names Product Number: 805877, 805628, 805629, 805936, 23179

### 1.2. Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Intended Use See Technical Data Sheet  
 Application Method See Technical Data Sheet

### 1.3. Details Of The Supplier Of The Safety Data Sheet

Distributor **#1 NETWORK, INC.** 307 Professional Park Ave. Effingham, IL 62401  
 CHEMTREC (USA) 800-424-9300  
 Customer Service 217-536-5737

## 2. Hazard Identification Of The Product

### 2.1. Classification Of The Substance Or Mixture

Flam. Liq. 2;	H225	Highly flammable liquid and vapor
Acute Tox. 4;	H302, H312, H332	Harmful if swallowed / Harmful in contact with skin / Harmful if inhaled
Skin Irrit. 2;	H315	Causes skin irritation
Eye Irrit. 2;	H319	Causes serious eye irritation
Repr. 2;	H361D	Suspected of damaging the unborn child
STOT SE 1;	H370	Causes damage to organs
STOT RE 2;	H373	May cause damage to organs through prolonged or repeated exposure

### 2.2. Label Elements

Using the Toxicity Data listed in Sections 11 and 12, the product is listed as follows:

Signal Word: **DANGER!**

H225 Highly flammable liquid and vapor  
 H302 Harmful if swallowed  
 H312 Harmful in contact with skin  
 H315 Causes skin irritation  
 H319 Causes serious eye irritation  
 H332 Harmful if inhaled  
 H361D Suspected of damaging the unborn child  
 H370 Causes damage to organs  
 H373 May cause damage to organs through prolonged or repeated exposure



### [ Prevention ]

P201 Obtain special instructions before use  
 P202 Do not handle until all safety precautions have been read and understood  
 P210 Keep away from heat, sparks, open flames, and hot surfaces - No smoking  
 P241 Use explosion-proof electrical, ventilation, lighting, and equipment  
 P261 Avoid breathing dust, fume, gas, mist, vapors, spray  
 P264 Wash thoroughly after handling  
 P270 Do not eat, drink or smoke when using this product  
 P271 Use only outdoors or in a well-ventilated area  
 P280 Wear protective gloves, eye protection, and face protection

### [ Response ]

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor, physician if you feel unwell  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove / take off immediately all contaminated clothing - Rinse skin with water & shower  
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305 + P351 + P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
 P307 + P311 IF exposed: Call a POISON CENTER or doctor / physician.  
 P308 + P313 IF exposed or concerned: Get medical advice / attention.  
 P314 Get Medical advice / attention if you feel unwell.  
 P321 Specific treatment (see information on this label)  
 P330 Rinse mouth  
 P337 + P313 If eye irritation persists: Get medical attention  
 P362 Take off contaminated clothing and wash before reuse  
 P363 Wash contaminated clothing before reuse  
 P370 + P378 In case of fire: Use extinguishing media listed in Section 5 of SDS for extinction

### [ Storage ]

P403 + P233 Store in a well ventilated area. Keep container tightly closed P405 Store locked up

### [ Disposal ]

P501 Dispose of contents and container in accordance with local and national regulations

**Safety Data Sheet: Network Glaze Clean: Deglazer & Calcium Deposit Remover**  
SDS Revision Date: 2/17/2015 • Pg. 2 of 8

### 3. Composition / Information On Ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient / Chemical Designations	Weight%	GHS Classification	Notes
Toluene (CAS No: 108-88-3)	50 - 55	Flam. Liq. 2: H225 Repr. 2: H361D Asp. Tox. 1: H304 STOT RE 2: H373 Skin Irrit. 2: H315 STOT SE 3: H336	[ 1 ][ 2 ]
Acetone (CAS No: 67-64-1)	20 - 25	Flam. Liq. 2: H225 Eye Irrit. 2: H319 STOT SE 3: H336	[ 1 ][ 2 ]
Methanol (CAS No: 67-56-1)	20 - 25	Flam. Liq. 2: H225 Acute Tox. 3: H331, H311, H301 STOT SE 1: H370	[ 1 ][ 2 ]

[ 1 ] Substance classified with a health or environmental hazard

[ 2 ] Substance with a workplace exposure limit

[ 3 ] PBT-Substance or vPvB-Substance

\* The full texts of the phrases are shown in Section 16

### 4. First Aid Measures

#### 4.1. Description Of First Aid Measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	<b>If chemical is swallowed, Call Physician Or Poison Control Center For Most Current Information. Ingestion is life threatening.</b> Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Victims Of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take copy of label and SDS with victim to health professional.

#### 4.2. Most Important Symptoms And Effects, Both Acute And Delayed

<b>Overview</b>	<p><b>Acute:</b> Severe irritation of the tissue that had contact with the product (skin, eyes, mucous membranes). Drowsiness, fatigue, confusion may be experienced after inhalation or ingestion of the material.</p> <p><b>Chronic:</b> Methanol is eliminated slowly from the body. Therefore repeated exposures may build up to toxic levels in body tissues. Animal studies shows long term exposures to Methanol damages the CNS, kidneys or liver, skin disorders, and birth defects.</p> <p><b>Symptoms of Over Exposure by Route of Exposure:</b> Methanol may be harmful if swallowed, inhaled, or injected into skin. Methanol can cause skin and eye irritation or damage. Methanol can be very irritating to mucous membranes and the respiratory tract.</p> <p><b>Inhalation:</b> Inhalation of Methanol vapors may lead to irritation of the nose and throat. Symptoms of overexposure may include dizziness, coughing, headache, dyspnea, lachrymation, nausea and vomiting. Exposure to high concentrations of this material vapor may cause unconsciousness or death.</p> <p><b>Primary Routes of Entry:</b> Inhalation, skin contact, eyes, ingestion.</p> <p><b>Target Organs:</b> CNS, eyes, circulatory and respiratory systems.</p> <p><b>Contact With Skin or Eyes:</b> Methanol is an eye and skin irritant. Splashes in the eye may cause eye irritation, redness, tearing, and temporary corneal damage or blindness.</p> <p><b>Skin Absorption:</b> Methanol is absorbed through the skin and may result in effects similar to inhalation exposure.</p> <p><b>Ingestion:</b> Ingestion of one to four ounces of Methanol can cause irreversible damage to the nervous system, blindness, or death. It cannot be made non-poisonous. Aspiration of the material into the lungs can cause chemical pneumonitis.</p> <p><b>Injection:</b> Injection of Methanol can lead to redness and irritation of the surrounding tissue.</p> <p><b>AGGRAVATED MEDICAL CONDITIONS:</b> Persons with pre-existing skin disorders or impaired liver or kidney function may be more susceptible to the effects of this substance. Alcoholic beverage consumption can enhance the toxic effects of this substance. Chronic fumes from this product may exacerbate asthma.</p> <p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue,</p>
-----------------	--

#### 4. First Aid Measures, Cont.'

muscular weakness, drowsiness and in extreme cases, loss of consciousness.  
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See Section 2 for further details.

<b>Inhalation</b>	Harmful if inhaled
<b>Eyes</b>	Causes serious eye irritation
<b>Skin</b>	Harmful in contact with skin. Causes skin irritation.
<b>Ingestion</b>	Harmful if swallowed

#### 5. Fire-Fighting Measures

##### 5.1. Extinguishing Media

Dry chemical, foam or carbon dioxide.

##### 5.2. Special Hazards Arising From The Substance Or Mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide. Keep away from heat, sparks, open flames, and hot surfaces - No smoking. Use explosion-proof electrical, ventilating, light, and equipment. Avoid breathing dust, fume, gas, mist, vapors, or spray.

##### 5.3. Advice For Firefighters

Above flashpoint, vapor-air mixtures are explosive within flammable limits noted above. Vapors are heavier than air and may travel along the ground to distant ignition sources and flash back. Contact with strong oxidizers may cause a fire. Risk of explosion in closed containers if pressure rises rapidly. May produce a floating fire hazard. Sensitive to static charge. The use of SCBA positive pressure self-contained breathing apparatus is recommended for firefighters and full protective clothing. Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

**ERG Guide No.** 128

#### 6. Accidental Release Measures

##### 6.1. Personal Precautions, Protective Equipment, And Emergency Procedures

Put on appropriate personal protective equipment (see Section 8).

##### 6.2. Environmental Precautions

Do not allow spills to enter drains or watercourses. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

##### 6.3. Methods And Material For Containment And Cleaning Up

Flammable material. Eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing. Use water to keep fire exposed containers cool and disperse vapors. Do not use sawdust. Use non-sparking tools. Place in non-leaking containers and seal tightly for proper disposal. CERCLA requires reporting spills in excess of RQ.

#### 7. Handling And Storage

##### 7.1. Precautions For Safe Handling

All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Triple rinse before disposal. Dispose of in a licensed facility. Recommended crushing or other means to prevent re-use. Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids. See Section 2 for further details [Prevention].

##### 7.2. Conditions For Safe Storage, Including Any Incompatibilities

Handle containers carefully to prevent damage and spillage. Incompatible materials: This substance is not compatible with strong oxidizing agents, acetyl bromide, alkylaluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and raney nickel catalyst. Flammable. Keep away from heat, sparks, and open flame. Store in a cool, dry, well-ventilated area. Keep containers closed. Do not store with incompatible materials, such as oxidizers. Protect from light, including direct sunlight. All five-gallon pails or larger should be grounded and/or bonded when material is transferred to eliminate static electric sparks. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment may result in ignitions. Do not store or consume food, drink, or tobacco where they may become contaminated with this material. Mechanical ventilation or local exhaust may be required. See Section 2 for further details [Storage].

##### 7.3. Specific End Use(s)

No data available.

**8. Exposure Controls And Personal Protection**

**8.1. Control Parameters**

CAS No.	Ingredient	EXPOSURE	
		Source	Value
67-56-1	Methanol	OSHA	TWA: 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm Skin
		NIOSH	TWA: 200 ppm (260 mg/m3) ST: 250 ppm (325 mg/m3) Skin
		Supplier	No Established Limit
67-64-1	Acetone	OSHA	TWA: 1000 ppm (2400 mg/m3) STEL: 2400 mg/m3
		ACGIH	TWA: 250 ppm STEL: 500 ppm Skin
		NIOSH	TWA: 250 ppm (590 mg/m3)
		Supplier	No Established Limit
108-88-3	Toluene	OSHA	TWA: 200 ppm C: 300 ppm 500 ppm (10-minute max peak) STEL: 150 ppm
		ACGIH	TWA: 20 ppm
		NIOSH	TWA: 100 ppm (375 mg/m3) ST: 150 ppm (560 mg/m3)
		Supplier	No Established Limit

CAS No.	Ingredient	CARCINOGEN DATA	
		Source	Value
67-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
67-64-1	Acetone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

**8.2. Description Of First Aid Measures**

<b>Respiratory</b>	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
<b>Eyes</b>	Chemical safety goggles with full face shield.
<b>Skin</b>	Wear overalls to keep skin contact to a minimum. Impervious gloves are recommended.
<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.  All electrical equipment should comply with the National Electrical code. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
<b>Other Work Practices</b>	If exposure limit is exceeded, a half-face organic vapor respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified. A full-face piece respirator organic vapor respirator may be worn up to 50 times the exposure limit. <b>WARNING:</b> Air-purifying respirators will not protect workers in oxygen-deficient atmospheres. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. See Section 2 for further details. [Prevention]

**Safety Data Sheet: Network Glaze Clean: Deglazer & Calcium Deposit Remover**  
 SDS Revision Date: 2/17/2015 • Pg. 5 of 8

**9. Physical And Chemical Properties**

**9.1.**

<b>Appearance</b>	Clear, colorless liquid	<b>Melting Point / Freezing Point</b>	Not Measured
<b>Odor</b>	Ketone	<b>Initial Boiling Point / Boiling Range</b>	133°F to 200°F
<b>Odor Threshold</b>	Not Measured	<b>Evaporation Rate (n-Butyl Acetate = 1)</b>	Not Measured
<b>Flashpoint</b>	< 0°F	<b>Upper / Lower Flammability or</b>	Lower: NA
<b>pH</b>	NA	<b>Explosive Limits</b>	Upper: NA
<b>Flammability (Solid, Gas)</b>	NA	<b>Partition Coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Vapor Pressure (PA) (Total)</b>	N.E. mm Hg @ 20°C	<b>Vapor Pressure (PA) (Acetone Exempt)</b>	48.9 mm Hg @ 20°C
<b>Vapor Density</b>	Not Measured	<b>Solubility In Water</b>	Negligible
<b>Specific Gravity</b>	0.83	<b>Auto-Ignition Temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured	<b>Decomposition Temperature</b>	Not Measured
<b>Density</b>	6.91 lbs per gallon	<b>% Volatile</b>	100
<b>Photochemically Reactive</b>	Yes	<b>V.O.C. (Total)</b>	828 gm/L, 100%, 6.91 lb/gal
<b>Max Grams of V.O.C./Ltr</b>	828	<b>V.O.C. (Acetone Exempt)</b>	634 gm/L, 76.4%, 5.28 lb/gal

**9.2. Other Information**

No other relevant information.

**10. Stability And Reactivity**

**10.1. Reactivity:** Hazardous Polymerization will not occur.

**10.2. Chemical Stability:** Stable under normal circumstances.

**10.3. Possibility Of Hazardous Reactions:** No data available.

**10.4. Conditions To Avoid:** Extreme heat may cause product to decompose, producing acrid smoke and irritating fumes.

**10.5. Incompatible Materials:** This substance is not compatible with strong oxidizing agents, acetyl bromide, alkylaluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and raney nickel catalyst.

**10.6. Hazardous Decomposition Products:** High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**11. Toxicological Information**

**Acute Toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-Butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

<b>Ingredient</b>	<b>Oral LD50 (mg/kg)</b>	<b>Skin LD50 (mg/kg)</b>	<b>Inhalation Vapor LD50 (mg/L/4hr)</b>	<b>Inhalation Dust/Mist LD50 (mg/L/4hr)</b>	<b>Inhalation Gas LD50 (ppm)</b>
Acetone 67-64-1	2,000.00 Rat Category: 4	2,000.00 Rabbit Category: 4	76.00 Rat Category: NA	No Data Available	No Data Available
Toluene 108-88-3	636.00 Rat Category: 4	8,400.00 Rabbit Category: NA	No Data Available	No Data Available	No Data Available
Methanol 67-56-1	143.00 Human Category: 3	No Data Available	No Data Available	No Data Available	64,000.00 Rat Category: NA

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

**11. Toxicological Information, Cont.'**

Classification	Category	Hazard Description
Acute Toxicity (oral)	4	Harmful if swallowed
Acute Toxicity (dermal)	4	Harmful in contact with skin
Acute Toxicity (inhalation)	4	Harmful if inhaled
Skin Corrosion / Irritation	2	Causes skin irritation
Serious Eye Damage / Irritation	2	Causes serious eye irritation
Respiratory Sensitization	---	Not Applicable
Skin Sensitization	---	Not Applicable
Germ Cell Mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive Toxicity	2	Suspected of damaging the unborn child
STOT - Single Exposure	---	Not Applicable
STOT - Repeated Exposure	2	May cause damage to organs through prolonged or repeated exposure
Aspiration Hazard	---	Not Applicable

**12. Ecological Information**

**12.1. Toxicity**

No additional information provided for this product. See Section 3 for chemical specific data.

**AQUATIC ECOTOXICITY**

Ingredient	96 Hr LC50 Fish (mg/L)	48 Hr EC50 Crustacea (mg/L)	ERC50 Algae (mg/L)
Acetone 67-64-1	100.00, Pimephales Promelas	10.00, Daphnia Magna	20.565 (72 Hr), Ulva Pertusa
Toluene 108-88-3	5.80, Onchorhynchus Mykiss	19.60, Daphnia Magna	Not Available
Methanol 67-56-1	100.00, Pimephales Promelas	10,000.00, Daphnia Magna	16.912 (96 Hr), Ulva Pertusa

**12.2. Persistence And Degradability:** There is no data available on the preparation itself.

**12.3. Bioaccumulative Potential:** Not Measured

**12.4. Mobility In Soil:** No data available.

**12.5. Results Of PBT And vPvB Assessment:** This product contains no PBT/vPvB chemicals.

**12.6. Other Adverse Effects:**

No data available.

**13. Disposal Considerations**

**13.1 Waste Treatment Methods**

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport Information

### NON-BULK DOMESTIC GROUND

This material is regulated for domestic ground shipments by the U.S. Department of Transportation (DOT) when transported in non-bulk (a packaging which has a maximum capacity of 119 gallons or less as a receptacle for a liquid). Reference 49 CFR 173.120 (b) (2) and 173.150 (f) (1).

In summary, for **non-bulk domestic ground shipments:**

**DOT Shipping Name:** UN 1263, Paint Related Material  
**Hazard Class:** 3  
**UN No.:** UN 1263  
**Packing Group:** III  
**Guide No:** 128

Additional Information: May be shipped as a LIMITED QUANTITY when transported in containers no larger than 1.0 L (0.3 gallons), in packages not exceeding 30 kg (66 lbs) gross mass. 49 CFR 173.150 (b)(2).

### BULK DOMESTIC GROUND

This material is not available for domestic ground shipment in bulk (a packaging which has a maximum capacity greater than 119 gallons as a receptacle for a liquid).

The domestic provisions provided for in non-bulk and bulk ground shipments are not valid for transportation by aircraft or vessel and they are not valid for international shipments. Please follow the appropriate DOT regulations in 49 CFR and the information referenced where appropriate in the IATA Dangerous Goods Transportation Regulation, the International Maritime Organization (IMO), the International Civil Aviation Organization (ICAO) and our NFTA partner hazardous material regulation requirements).

### OCEAN TRANSPORTATION

In summary, for **ocean shipments:**

**Proper Shipping Name:** UN 1263, Paint Related Material  
**UN No.:** UN 1263  
**Packing Group:** III  
**IMDG:** 3  
**Environmental Hazards:** IMDG: Marine Pollutant: Yes

**14.6. Special Precautions For User:** No further information

## 15. Regulatory Information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**TSCA** All listed components either appear or are exempt from the Toxic Substances Control Act (TSCA) Inventory.

**CERCLA** Acetone, Toluene, and Methanol are listed.

**Carcinogenicity** None of the components in this chemical are present above minimum amounts listed by IARC, NTP, or OSHA as a carcinogen.

**WHMIS Classification** B2, D2A

**US EPA Tier II Hazards** **Fire:** Yes **Sudden Release of Pressure:** No **Reactive:** No **Immediate (Acute):** Yes **Delayed (Chronic):** Yes

**SARA Title III** <sup>1</sup> Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372. This product contains: Methanol (Cas # 95-63-6) and Toluene (Cas # 100-41-4).

**California PROP 65:** This product contains Toluene. The following information is required by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986, or Proposition 65. This regulation does not address di minimus levels; therefore, even trace amounts of the chemicals included on Proposition 65's list of chemicals known to the State of California to cause cancer or reproductive toxicity must be noted with the "Safe Harbor" wording. **WARNING:** This product contains Toluene known to the State of California to cause birth defects, or other reproductive harm.

**EPCRA 311/312 Chemicals and RQs (Lbs):** Acetone (5,000), Methanol (5,000), Toluene (1,000)

**EPCRA 302 Extremely Hazardous:** None Listed

**Proposition 65 - Carcinogens (>0.0%):** Listed Above

**Proposition 65 - Female Repro Toxins (>0.0%):** Listed Above

**N.J. RTK Substances (>1%):** Acetone, Methanol, Toluene

**EPCRA 313 Toxic Chemicals:** Methanol, Toluene

**Proposition 65 - Developmental Toxins (>0.0%):** Listed Above

**Proposition 65 - Male Repro Toxins (>0.0%):** Listed Above

**Penn RTK Substances (>1%) :** Acetone, Methanol, Toluene

## 16. Other Information

### HMIS

Health: 3  
Flammability: 3  
Reactivity: 0  
Protective: B

### SCAQMD Rule 443.1

Photochemically Reactive: No  
Maximum Grams of VOC per Liter: 48.9 gm/L (Acetone Exempt)  
Vapor Pressure: 634 mm Hg @ 20°C (Acetone Exempt)

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

### The full text of the phrases appearing in section 3 is:

**H225** Highly flammable liquid and vapor  
**H301** Toxic if swallowed  
**H304** May be fatal if swallowed and enters airways  
**H311** Toxic in contact with skin  
**H315** Causes skin irritation  
**H319** Causes serious eye irritation  
**H331** Toxic if inhaled  
**H336** May cause drowsiness and dizziness  
**H361D** Suspected of damaging the unborn child  
**H370** Causes damage to organs  
**H373** May cause damage to organs through prolonged or repeated exposure

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

This Safety data Sheet was prepared using information provided by/obtained from Böttcher America. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. Böttcher America expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of Böttcher America.